



บริษัท โปร-แมคคัลนิคส์ จำกัด
PRO-MECHANIC CO.,LTD.

WWW.PROMECHANIC.CO.TH

PRO MEC RING BLOWER



Single stage blower models and performance(IP54 50/60HZ three phase)

curve No	MODEL	Freq Hz	Output power Kw	voltage V	Rated current A	Max airflow m3/h	Max static suction mbar	Max static pressure mbar	Noise dB(A)	Net Weight Kg
N15	NVT-020	50	0.2	220-240 Δ 380-415Y	1.0 Δ/0.6Y	40	-60	70	50	6
N16		60	0.23	220-240 Δ 380-415Y	1.0 Δ/0.6Y	55	-60	70	51	6
N25	NVT-040	50	0.4	220-240 Δ 380-415Y	2.5 Δ/1.3Y	80	-120	130	53	10
N26		60	0.5	220-240 Δ 380-415Y	3.4 Δ/2.0Y	98	-150	160	56	10
N35	NVT-085	50	0.85	220-240 Δ 380-415Y	4.2 Δ/2.4Y	145	160	160	63	15
N36		60	0.95	220-240 Δ 380-415Y	4.0 Δ/2.3Y	175	160	160	64	15
N45	NVT-160	50	1.6	220-240 Δ 380-415Y	7.5 Δ/4.3Y	210	-200	190	64	21
N46		60	2.1	220-240 Δ 380-415Y	7.6 Δ/4.4Y	255	-220	210	70	21
N55	NVT-220	50	2.2	220-240 Δ 380-415Y	10 Δ/5.6Y	318	-210	200	69	29
N56		60	2.55	220-240 Δ 380-415Y	10.3Δ/6.5Y	376	-210	220	72	29
N65	NVT-400	50	4	380-415 Δ	9.5 Δ	318	-290	330	69	42
N66		60	4.6	380-415 Δ	9.5 Δ	376	-330	330	72	42
N75	NVT-550	50	5.5	380-415 Δ	13.3 Δ	450	-300	320	80	65
N76		60	6.3	380-415 Δ	13.3 Δ	500	-320	340	82	65
N85	NVT-750	50	7.5	380-415 Δ	16.7 Δ	450	-320	380	80	68
N86		60	8.6	380-415 Δ	17.3 Δ	500	-340	400	82	68

Single stage blower models and performance(IP54 50/60HZ single phase)

curve No	MODEL	Freq Hz	Output power Kw	voltage V	Rated current A	Max airflow m3/h	Max static suction mbar	Max static pressure mbar	Noise dB(A)	Net Weight Kg
N15S	NVS-020	50	0.2	200-240V	1.43	40	-60	70	50	6
N16S		60	0.23	200-240V	1.3	55	-60	70	51	6
N25S	NVS-040	50	0.4	200-240V	2.7	80	-120	130	53	9
N26S		60	0.5	200-240V	3.2	98	-150	160	56	9
N35S	NVS-085	50	0.85	200-240V	5	145	160	160	63	16
N36S		60	0.95	200-240V	5.8	175	160	160	64	16
N45S	NVS-160	50	1.5	200-240V	9.8	210	-200	190	64	24
N46S		60	1.75	200-240V	10.5	255	-220	210	70	24

